CISC105 Midterm 1 Sample Questions from Previous Exams

NAME _____

General instructions:

There are problems worth a total of points . Read the problems very carefully. Identify what kind of answer the problem asks for. Carefully look at requirements for input and output, and any restrictions on how your code must be written.

You may assume that input will not produce errors for the procedures described, unless the questions says otherwise.

Do problems you are confident about first. If you finish the problems you know, write what you do know about other problems to gain partial credit; but erroneous information may detract from that credit or irritate the grader, so don't make stuff up.

Do not do unnecessary testing. For example, testing for both x < 0 and $x \ge 0$ instead of using one test and then else would be considered unnecessary testing.

Do not make code unnecessarily inefficient.

Short answer. Use only the space provided.

- 1. What values are true in C?
- 2. What does the C statement "int q;" do inside the computer, as discussed in class?
- 3. Is #include a reserved word in C? Explain your answer very briefly.
- 4. When would you use a sentinel-controlled loop?
- 5. (6 pts) Write two complete examples, one of each of the preprocessor directives we have reviewed in class.
- 6. What is the main issue, as discussed in class, that you must consider when choosing a sentinel?
- 7. Structured programming says that all programs can be written using a combination of three kinds of control structures. What are they?
- 8. You are told to write some code that will execute 100,000 times. As discussed in class, which type of loop should you probably use?

- 9. You are told to write a sentinel-controlled loop. As discussed in class, which type of loop should you probably use?
- 10. You are told to write a loop that runs until the user enter a Carmichael number. As discussed in class, which type of loop should you probably use?
- 11. (6 pts) Write two complete examples, one of each of the preprocessor directives we have reviewed in class.
- 12. (4 pts) When you load a C program, what physical part of the computer does it *come* from?
- 13. (6 pts) What are the structures we have studied in class so far for accomplishing selection of code in C?
- 14. (12 pts) Write the appropriate shell command next to each task:
 - (a) compile a C program
 - (b) list the contents of a file
 - (c) show the location of the current directory
 - (d) create a new directory
 - (e) make a copy of a file
- 15. (4 pts) What is binary 1001001101011010 in hex?
- 16. (4 pts) What is binary 1101101 in decimal?
- 17. (4 pts) What is decimal 567 in hex?
- 18. (4 pts) What is decimal 322 in binary?

- 19. (4 pts) Advocates of this philosophy proved that all programming could be done using only sequence, selection, and repetition. What is its name?
- 20. (4 pts) Write the binary equivalent of the decimal number 157.
- 21. (10 pts) Write a for loop using the variable provided that prints the following output:

22. 12 pts. Write the six stages of a C program in order. Next to each, write the shell command that accomplishes it.

For the next section, choose the letter that shows the value that would be in x. Assume x and y are declared as integers. Choose "error" if you think a fragment will not compile and run. The fragments are unrelated (each question is separate from the others). HINT: Calculate your answer before you look at the selections.

```
23. (2 pts)
```

x = 2 - 3 * 2 - 7;(a) 5 (b) 11 (c) 2 (d) error (e) none of the above 24. (2 pts) x = 2 + 3 || 2 < 3;(a) 5 (b) 0 (c) 1 (d) error (e) none of the above 25. (2 pts) y = 3.6; x = (double)y * 2;(a) 7.2 (b) 7 (c) 6 (d) error (e) none of the above 26. (2 pts) x = 15 % 3;

(a) 5 (b) 1 (c) 3 (d) error (e) none of the above

27. (2 pts) x = 6 % 7;(a) 1 (b) 7 (c) 6 (d) error (e) none of the above 28. (2 pts) x = 3 / 4 && 4 / 3;(a) 0 (b) 1 (c) 12 (d) error (e) none of the above 29. (2 pts) y = 30 == 3;x = !y;(a) 1 (b) 0 (c) 27 (d) -1 (e) error 30. (2 pts) x = (8 > 5 > 4);(a) false (b) 1 (c) 0 (d) error (e) none of the above 31. (2 pts) y = 0 >= 0;x = !y;(a) 1 (b) -1 (c) 0 (d) error (e) none of the above 32. (2 pts) x = 8;x *= 2; (a) 4 (b) 8 (c) 16 (d) error (e) none of the above 33. (2 pts) x = 0 / 10110110;(a) 1 (b) 6 (c) 0 (d) error (e) none of the above 34. (2 pts) x = 11 / 3;

(a) 3 (b) 2 (c) 3.333 (d) error (e) none of the above 35. (2 pts) y = 15 / 16;x = 16 / y;(a) 15 (b) 1 (c) pi (d) error (e) none of the above 36. (2 pts) double z = 8;x = 8 || z/12;(a) 0 (b) 1 (c) 0.66 (d) error (e) none of the above 37. (2 pts) double z = 10;x = z / 4.0;(a) .5 (b) 2.5 (c) 2 (d) error (e) none of the above 38. (2 pts) x = 3 < 2;x++; (a) 0 (b) 4 (c) 3 (d) error (e) none of the above 39. (2 pts) Which of the following assigns the value of 2 times y to x? (a)x = 2 * y; (b) 2 * y = x; (c) x = 2 x y; (d) x = 2 * y;40. (2 pts) The load stage of a C program is accomplished by which command? (a) emacs (b) a.out (c) pwd (d) gcc (e) none of the above 41. (2 pts) The link stage of a C program is accomplished by which command? (a) emacs (b) a.out (c) pwd (d) gcc (e) none of the above 42. (2 pts) The preprocess stage of a C program is accomplished by which command? (a) emacs (b) a.out (c) pwd (d) gcc (e) none of the above 43. (2 pts) The execute stage of a C program is accomplished by which command? (b) a.out (c) pwd (d) gcc (e) none of the above (a) emacs

44. (2 pts) The edit stage of a C program is accomplished by which command?

(a) emacs (b) a.out (c) pwd (d) gcc (e) none of the above

- 45. (4 pts) Which of the following correctly orders memory speed from slowest to fastest?
 - (a) disk cache RAM registers
 - (b) disk RAM cache registers
 - (c) RAM disk cache registers
 - (d) cache RAM disk registers
 - (e) none of the above
- 46. (3 pts) Which kind of memory is built into the CPU?
 - (a) registers
 - (b) ALU
 - (c) cache
 - (d) RAM
 - (e) none of the above

Use these choices to relate classroom discussions to the next four questions:

- (a) measured in Kilobytes
- (b) extremely fast, very high cost per byte
- (c) a chip connected to the CPU via the bus
- (d) very slow, but lowest cost per byte
- (e) none of the above
- 47. (3 pts) The best description to associate with disk is:
- 48. (3 pts) The best description to associate with cache is:
- 49. (3 pts) The best description to associate with ALU is:
- 50. (3 pts) The best description to associate with RAM is:

For the next section, choose the letter that shows the value that would be in x. Assume x and y are declared as integers. Choose "error" if you think a fragment will not compile and run. The fragments are unrelated (each question is separate from the others).

(a) (2 pts)
x = 3 + 3 * 2 - 7;
(a) 5 (b) 11 (c) 2 (d) error (e) none of the above
(b) (2 pts)
x = -4 || 0;

(a) 0 (b) -4 (c) -1 (d) error (e) none of the above (c) (2 pts) y = 0; x = y++;(a) 1 (b) 2 (c) 0 (d) error (e) none of the above (d) (2 pts) x = 5 % 3;(a) 2 (b) 1 (c) 3 (d) error (e) none of the above (e) (2 pts) x = 2 % 3;(a) 1 (b) 0 (c) 3 (d) error (e) none of the above (f) (2 pts) x = 14 % 7;(a) 0 (b) 2 (c) 4 (d) error (e) none of the above (g) (2 pts) y = 30 != 3;x = -3 && !y;(a) 1 (b) 0 (c) 27 (d) -3 (e) error (h) (2 pts) x = (8 < 15 < 4);(a) false (b) 1 (c) 0 (d) error (e) none of the above (i) (2 pts) y = 0 >= 1;x = !y;(a) 1 (b) -1 (c) 0 (d) error (e) none of the above (j) (2 pts) x = 8;x += 2; (a) 2 (b) 8 (c) 6 (d) error (e) none of the above (k) (2 pts) x = 0 / 6;(a) 1 (b) 6 (c) 0 (d) error (e) none of the above

(l) (2 pts) x = 14 / 4;(a) 3 (b) 2 (c) 3 (d) error (e) none of the above (m) (2 pts) y = 5 / 6;x = 2 / y;(a) 5 (b) 11 (c) -8 (d) error (e) none of the above (n) (2 pts) y = 4.4;x = y * 2;(a) 8 (b) 8.8 (c) 2 (d) error (e) none of the above (o) (2 pts) float z = 8;x = z/12;(a) 1.5 (b) 1 (c) 0.75 (d) error (e) none of the above (p) (2 pts) float z = 18;x = z / 12.0;(a) 1.5 (b) 1 (c) 0.75 (d) error (e) none of the above (q) (2 pts) x = 3 < 2;x = 3 / x;(b) 1 (c) 3 (d) error (e) none of the above (a) 0

(r) 26 pts. Write the value of x after each of the following code fragments, OR write ERROR if you think a fragment will not compile and run. The fragments are unrelated. Assume x and y are declared as integers. If you write calculations, be sure the eventual answer is circled so that I can find it.

i. y = 5; x = y++;
ii. x = 3 + 4 * 2 - 12;
iii. x = 3 || 4;

xx. x = 4; x += 5; xxi. x = 15 / 6; xxii. x = 5 / 0; xxiii. x = 0 / 5;

- (s) 32 pts. Write code fragments that will generate *exactly* the output shown. Follow the instructions carefully. DECLARE ANY VARIABLES YOU NEED. You may write next to the output so that you have more space.
 - i. Write a while loop to generate this output:
 - 1 2 3 4

ii. Write a while loop to generate this output:2 4 6 8

iii. Write a loop to generate this output: $-50 \ 0 \ 50 \ 100 \ 150$

- iv. Write a single loop to generate this output. Print only a *single* asterisk at a time. You may use only two printfs total.
 - *** *** ***

v. Write a loop to generate this output: $-5 \ 0 \ 5 \ 10 \ 15$

- i. 15 pts. Write a whole program that prompts the user for a value, reads the value into a variable, then prints the number out and stops.
- ii. 20 pts. Write a switch statement that will print "green" for input integers 0-3; "red" for 4-7; "yellow" for 8-11; and "purple" for any other integer. You may not use more than four different cases. Assume the input is already in the declared integer variable "input".
- iii. 30 pts. Write a whole program using if, else, and other C code so that it behaves as follows:

```
shell% a.out
Enter a positive integer: 7
7 is less than 10!
Enter a positive integer: 8
8 is less than 10!
Enter a positive integer: 11
11 is not less than 10.
Enter a positive integer: -1
bye!
shell%
```

- iv. 30 pts. Write a whole program that behaves as follows: Prompt the user for an integer, one thousand times. Then show the user the average of those numbers, the highest number, and the lowest number.
- v. 15 pts. Write a main() function that
 - A. declares two variables
 - B. initializes them to the numbers 4.7 and 7.8
 - C. adds them together
 - D. prints the sum of the two
 - E. stops.
- vi. 30 pts. Write a whole program that behaves as follows: Prompt the user for an integer, one hundred times. Each time through the loop, show the highest number so far, the lowest number so far, and the average of all input so far.
- vii. 20 pts. Write a switch statement with no more than five cases that behaves as follows. READ THE OUTPUT VERY CAREFULLY! The results are not an obvious pattern. All possible cases are shown in the output. Assume the input is already in the declared integer variable "input".

```
strauss% a.out
Enter a positive integer, or -1 to stop:
5
```

5 is less than 20 Enter a positive integer, or -1 to stop: 35 35 is less than 40 Enter a positive integer, or -1 to stop: 55 55 is less than 60 Enter a positive integer, or -1 to stop: 61 61 is less than 100 Enter a positive integer, or -1 to stop: 85 85 is less than 100 Enter a positive integer, or -1 to stop: 106 106 is equal to or more than 100 Enter a positive integer, or -1 to stop: -1 strauss%

- i. 15 pts. Write a whole program that prompts the user for a value, reads the value into a variable, then prints the number out and stops.
- ii. 15 pts. Write a main() function that
 - A. declares two variables
 - B. initializes them to the numbers 4.7 and 7.8
 - C. adds them together
 - D. prints the sum of the two
 - E. stops.
- iii. 30 pts. Write a whole program that behaves as follows: Prompt the user for an integer, one hundred times. Each time through the loop, show the highest number so far, the lowest number so far, and the average of all input so far.
- iv. 18 pts. Short answer. Use only the space provided.
 - A. What values are false in C?
 - B. What values are true in C?
 - C. Write a complete example of a preprocessor statement.
 - D. What are the structures we have studied in class so far for accomplishing repetition of code in C?
 - E. Emacs, pico, and vi are all examples of what?
 - F. Structured programming says that all programs can be written using a combination of three kinds of control structures. What are they?

- G. Of the six stages of a C program discussed in class, which stages are accomplished by the shell command "gcc lab1.c"?
- H. You are told to write some code that will execute 100 times. As discussed in class, which type of loop should you probably use?
- I. When you load a C program as discussed in class, what physical part of the computer does it go to?
- v. 20 pts. Write the value of x after each of the following code fragments, OR write ERROR if you think a fragment will not compile and run. The fragments are unrelated. Assume x and y are declared as integers.

```
A. y = 5;
   x = y++;
B. x = 3 + 4 + 2 - 12;
C. x = 3 || 4;
D. y = 3 != 3;
   x = 3 \&\& y;
E. x = (3 < 5 < 2);
F. y = 0 >= 1;
   x = !y;
G. x = 5 \% 3;
H. x = 8;
   x += 2;
I. x = 11 / 6;
J. y = 5 / 6;
   x = 2 / y;
```

vi. 32 pts. Write code fragments that will generate *exactly* the output shown.Follow the instructions carefully. DECLARE ANY VARIABLES YOU NEED.You may write next to the output so that you have more space.A. Write a loop to generate this output:

 $1\ 2\ 3\ 4$

- B. Write a for loop to generate this output:
 - 3 2 1
 - 0

- C. Write a single loop to generate this output:
 - ***** ***** ***** *****

D. Write a loop to generate this output:-50 0 50 100 150

- vii. 20 pts. Write a switch statement that will print "green" for input integers 0-3; "red" for 4-7; "yellow" for 8-11; and "purple" for any other integer. You may not use more than four different cases. Assume the input is already in the declared integer variable "input".
- viii. 30 pts. Write a whole program using if, else, and other C code so that it behaves as follows: shell% a.out Enter a positive integer: 7 7 is less than 10! Enter a positive integer: 8

```
8 is less than 10!
Enter a positive integer: 11
11 is not less than 10.
Enter a positive integer: -1
bye!
shell%
```

- ix. 30 pts. Write a whole program that behaves as follows: Prompt the user for an integer, one thousand times. Then show the user the average of those numbers, the highest number, and the lowest number.
- x. Suppose you wanted to create a directory called "labs" to put all of your lab code in. Show how to create this directory.

60 pts. Multiple Choice: use the scan sheet for your answers.

xi. (2 pts) Which of the following assigns the value of 2 times y to x? (a)x = 2 * y; (b) 2 * y = x; (c) x = 2 x y; (d) x = 2 * y; xii. (2 pts) The load stage of a C program is accomplished by which command? (a) emacs (b) a.out (c) pwd (d) gcc (e) none of the above xiii. (2 pts) The link stage of a C program is accomplished by which command? (a) emacs (b) a.out (c) pwd (d) gcc (e) none of the above xiv. (2 pts) The preprocess stage of a C program is accomplished by which command? (a) emacs (b) a.out (c) pwd (d) gcc (e) none of the above xv. (2 pts) The execute stage of a C program is accomplished by which command? (b) a.out (c) pwd (d) gcc (e) none of the above (a) emacs xvi. (2 pts) The edit stage of a C program is accomplished by which command? (b) a.out (c) pwd (d) gcc (e) none of the above (a) emacs For the next section, choose the letter that shows the value that would be in x. Assume x and y are declared as integers. Choose "error" if you think a fragment will not compile and run. The fragments are unrelated (each question is separate from the others). xvii. (2 pts) x = 3 + 3 * 2 - 7;(a) 5 (b) 11 (c) 2 (d) error (e) none of the above

xviii. (2 pts)

x = 5 % 3;(a) 2 (b) 1 (c) 3 (d) error (e) none of the above xxi. (2 pts) x = 2 % 3;(b) 0 (c) 3 (d) error (e) none of the above (a) 1 xxii. (2 pts) x = 14 % 7;(b) 2 (c) 4 (d) error (e) none of the above (a) 0 xxiii. (2 pts) y = 30 != 3;x = -3 && !y;(a) 1 (b) 0 (c) 27 (d) -3 (e) error xxiv. (2 pts) x = (8 < 15 < 4);(a) false (b) 1 (c) 0 (d) error (e) none of the above xxv. (2 pts)y = 0 >= 1;x = !y;(a) 1 (b) -1 (c) 0 (d) error (e) none of the above xxvi. (2 pts) x = 8;x += 2; (b) 8 (c) 6 (d) error (e) none of the above (a) 2 xxvii. (2 pts) x = 0 / 6;(a) 1 (b) 6 (c) 0 (d) error (e) none of the above xxviii. (2 pts) x = 14 / 4;(a) 3 (b) 2 (c) 3 (d) error (e) none of the above xxix. (2 pts) y = 5 / 6;x = 2 / y;(b) 11 (c) -8 (d) error (e) none of the above (a) 5 xxx. (2 pts) y = 4.4;x = y * 2;(b) 8.8 (c) 2 (d) error (e) none of the above (a) 8 xxxi. (2 pts) float z = 8;x = z/12;(a) 1.5 (b) 1 (c) 0.75 (d) error (e) none of the above xxxii. (2 pts)

float z = 18; x = z / 12.0; (a) 1.5 (b) 1 (c) 0.75 (d) error (e) none of the above xxxiii. (2 pts) x = 3 < 2; x = 3 / x; (a) 0 (b) 1 (c) 3 (d) error (e) none of the above

i. (18 pts) Write code fragments that will generate *exactly* the output shown. Follow the instructions carefully. DECLARE ANY VARIABLES YOU NEED. You may write next to the output so that you have more space.

A. Write a loop to generate this output:

- B. Write a single loop to generate this output. You may only print a single asterisk in each pass of the loop:
 - ***** ***** *****

- ii. (20 pts) Write a whole program that behaves as follows: Prompt the user for two integers and print the average of the two integers.
- iii. (15 pts) Write a switch statement that will print "green" for input integers 0,3,6; "red" for 1,4,7; "mauve" for 2,5,8; and "blue" for any other positive integer. You may not use more than four different cases. Assume the input is already in the declared integer variable "input".
- iv. Extra Credit:
 - A. What is the emacs keyboard shortcut to open a file?
 - B. To save a file?
 - C. To indent a whole region of code at once?