

E04UQF – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

To supply optional parameters to E04UNF or E04UPF from an external file.

2 Specification

```
SUBROUTINE E04UQF(IOPTNS, INFORM)
  INTEGER          IOPTNS, INFORM
```

3 Description

E04UQF may be used to supply values for optional parameters to E04UNF or E04UPF. E04UQF reads an external file and each line of the file defines a single optional parameter. It is only necessary to supply values for those parameters whose values are to be different from their default values.

Each optional parameter is defined by a single character string of up to 72 characters, consisting of one or more items. The items associated with a given option must be separated by spaces, or equal signs [=]. Alphabetic characters may be upper or lower case. The string

```
Print level = 1
```

is an example of a string used to set an optional parameter. For each option the string contains one or more of the following items:

- (a) A mandatory keyword.
- (b) A phrase that qualifies the keyword.
- (c) A number that specifies an INTEGER or *real* value. Such numbers may be up to 16 contiguous characters in Fortran 77's I, F, E or D formats, terminated by a space if this is not the last item on the line.

Blank strings and comments are ignored. A comment begins with an asterisk (*) and all subsequent characters in the string are regarded as part of the comment.

The file containing the options must start with **begin** and must finish with **end**. An example of a valid options file is:

```
Begin * Example options file
  Print level = 5
End
```

Normally each line of the file is printed as it is read, on the current advisory message unit (see X04ABF), but printing may be suppressed using the keyword **nolist**. To suppress printing of **begin**, **nolist** must be the first option supplied as in the file:

```
Begin
  Nolist
  Print level = 5
End
```

Printing will automatically be turned on again after a call to E04UNF or E04UPF and may be turned on again at any time by the user by using the keyword **list**.

Optional parameter settings are preserved following a call to E04UNF or E04UPF, and so the keyword **defaults** is provided to allow the user to reset all the optional parameters to their default values prior to a subsequent call to E04UNF and E04UPF.

A complete list of optional parameters, their abbreviations, synonyms and default values is given in Section 11 of the documents for E04UNF and E04UPF.

4 References

None.

5 Parameters

1: IOPTNS — INTEGER *Input*

On entry: the unit number of the options file to be read.

Constraint: $0 \leq \text{IOPTNS} \leq 99$.

2: INFORM — INTEGER *Output*

On exit: contains zero if an options file with the correct structure has been read and a value > 0 otherwise, as indicated below.

INFORM = 1

IOPTNS is not in the range $[0, 99]$.

INFORM = 2

begin was found, but end-of-file was found before **end** was found.

INFORM = 3

end-of-file was found before **begin** was found.

6 Error Indicators and Warnings

If a line is not recognized as a valid option, then a warning message is output on the current advisory message unit (see X04ABF).

7 Accuracy

Not applicable.

8 Further Comments

E04URF may also be used to supply optional parameters to E04UNF or E04UPF.

9 Example

This example solves the same problem as the example for E04UNF, but in addition illustrates the use of E04UQF and E04URF to set optional parameters for E04UNF.

In this example the options file read by E04UQF is appended to the data file for the program (see Section 9.2). It would usually be more convenient in practice to keep the data file and the options file separate.

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```

*      E04UQF Example Program Text
*      Mark 17 Release. NAG Copyright 1995.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER        (NIN=5,NOUT=6)
      INTEGER          MMAX, NMAX, NCLMAX, NCNMAX
      PARAMETER        (MMAX=50,NMAX=10,NCLMAX=10,NCNMAX=10)
      INTEGER          LDA, LDCJ, LDFJ, LDR
      PARAMETER        (LDA=NCLMAX,LDCJ=NCNMAX,LDFJ=MMAX,LDR=NMAX)
      INTEGER          LIWORK, LWORK
      PARAMETER        (LIWORK=100,LWORK=1000)
*      .. Local Scalars ..
      real             OBJF
      INTEGER          I, IFAIL, INFORM, ITER, J, M, N, NCLIN, NCNLN
*      .. Local Arrays ..
      real             A(LDA,NMAX), BL(NMAX+NCLMAX+NCNMAX),
+                     BU(NMAX+NCLMAX+NCNMAX), C(NCNMAX),
+                     CJAC(LDCJ,NMAX), CLAMDA(NMAX+NCLMAX+NCNMAX),
+                     F(MMAX), FJAC(LDFJ,NMAX), R(LDR,NMAX), USER(1),
+                     WORK(LWORK), X(NMAX), Y(MMAX)
      INTEGER          ISTATE(NMAX+NCLMAX+NCNMAX), IUSER(1),
+                     IWORK(LIWORK)
*      .. External Subroutines ..
      EXTERNAL         CONFUN, E04UNF, E04UQF, E04URF, OBJFUN, X04ABF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'E04UQF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) M, N
      READ (NIN,*) NCLIN, NCNLN
      IF (M.LE.MMAX .AND. N.LE.NMAX .AND. NCLIN.LE.NCLMAX .AND.
+       NCNLN.LE.NCNMAX) THEN
*
*         Read A, Y, BL, BU and X from data file
*
         IF (NCLIN.GT.0) READ (NIN,*) ((A(I,J),J=1,N),I=1,NCLIN)
         READ (NIN,*) (Y(I),I=1,M)
         READ (NIN,*) (BL(I),I=1,N+NCLIN+NCNLN)
         READ (NIN,*) (BU(I),I=1,N+NCLIN+NCNLN)
         READ (NIN,*) (X(I),I=1,N)
*
*         Set three options using E04URF
*
         CALL E04URF(' Infinite Bound Size = 1.0D+25 ')
*
         CALL E04URF(' Print Level = 1 ')
*
         CALL E04URF(' Verify Level = -1 ')
*
*         Set the unit number for advisory messages to NOUT
*
         CALL X04ABF(1,NOUT)
*
*         Read the options file for the remaining options

```

```

*
      CALL E04UQF(NIN,INFORM)
*
      IF (INFORM.NE.0) THEN
        WRITE (NOUT,99999) 'E04UQF terminated with INFORM = ',
+          INFORM
        STOP
      END IF
*
      Solve the problem
*
      IFAIL = -1
*
      CALL E04UNF(M,N,NCLIN,NCNLN,LDA,LDCJ,LDFJ,LDR,A,BL,BU,Y,CONFUN,
+          OBJFUN,ITER,ISTATE,C,CJAC,F,FJAC,CLAMDA,OBJF,R,X,
+          IWORK,LIWORK,WORK,LWORK,IUSER,USER,IFAIL)
*
      END IF
      STOP
*
99999 FORMAT (1X,A,I3)
      END
      SUBROUTINE OBJFUN(MODE,M,N,LDFJ,X,F,FJAC,NSTATE,IUSER,USER)
*      Routine to evaluate the subfunctions and their 1st derivatives.
*      .. Parameters ..
      real                PT49, ONE, EIGHT
      PARAMETER          (PT49=0.49e0,ONE=1.0e0,EIGHT=8.0e0)
*      .. Scalar Arguments ..
      INTEGER            LDFJ, M, MODE, N, NSTATE
*      .. Array Arguments ..
      real                F(*), FJAC(LDFJ,*), USER(*), X(N)
      INTEGER            IUSER(*)
*      .. Local Scalars ..
      real                AI, TEMP, X1, X2
      INTEGER            I
      LOGICAL            MODE02, MODE12
*      .. Local Arrays ..
      real                A(44)
*      .. Intrinsic Functions ..
      INTRINSIC          EXP
*      .. Data statements ..
      DATA              A/8.0e0, 8.0e0, 10.0e0, 10.0e0, 10.0e0, 10.0e0,
+          12.0e0, 12.0e0, 12.0e0, 12.0e0, 14.0e0, 14.0e0,
+          14.0e0, 16.0e0, 16.0e0, 16.0e0, 18.0e0, 18.0e0,
+          20.0e0, 20.0e0, 20.0e0, 22.0e0, 22.0e0, 22.0e0,
+          24.0e0, 24.0e0, 24.0e0, 26.0e0, 26.0e0, 26.0e0,
+          28.0e0, 28.0e0, 30.0e0, 30.0e0, 30.0e0, 32.0e0,
+          32.0e0, 34.0e0, 36.0e0, 36.0e0, 38.0e0, 38.0e0,
+          40.0e0, 42.0e0/
*      .. Executable Statements ..
      X1 = X(1)
      X2 = X(2)
      MODE02 = MODE .EQ. 0 .OR. MODE .EQ. 2
      MODE12 = MODE .EQ. 1 .OR. MODE .EQ. 2
      DO 20 I = 1, M
        AI = A(I)
        TEMP = EXP(-X2*(AI-EIGHT))
        IF (MODE02) F(I) = X1 + (PT49-X1)*TEMP

```

```

      IF (MODE12) THEN
        FJAC(I,1) = ONE - TEMP
        FJAC(I,2) = -(PT49-X1)*(AI-EIGHT)*TEMP
      END IF
20  CONTINUE

*
      RETURN
      END

*
      SUBROUTINE CONFUN(MODE,NCNLN,N,LDCJ,NEEDC,X,C,CJAC,NSTATE,IUSER,
+          USER)
*
      Routine to evaluate the nonlinear constraint and its 1st
*
      derivatives.
*
      .. Parameters ..
      real                ZERO, PT09, PT49
      PARAMETER          (ZERO=0.0e0,PT09=0.09e0,PT49=0.49e0)
*
      .. Scalar Arguments ..
      INTEGER            LDCJ, MODE, N, NCNLN, NSTATE
*
      .. Array Arguments ..
      real                C(*), CJAC(LDCJ,*), USER(*), X(N)
      INTEGER            IUSER(*), NEEDC(*)
*
      .. Local Scalars ..
      INTEGER            I, J
*
      .. Executable Statements ..
      IF (NSTATE.EQ.1) THEN
*
        First call to CONFUN.  Set all Jacobian elements to zero.
*
        Note that this will only work when 'Derivative Level = 3'
*
        (the default; see Section 11.2).
        DO 40 J = 1, N
          DO 20 I = 1, NCNLN
            CJAC(I,J) = ZERO
          20  CONTINUE
        40  CONTINUE
      END IF

*
      IF (NEEDC(1).GT.0) THEN
        IF (MODE.EQ.0 .OR. MODE.EQ.2) C(1) = -PT09 - X(1)*X(2) +
+          PT49*X(2)
        IF (MODE.EQ.1 .OR. MODE.EQ.2) THEN
          CJAC(1,1) = -X(2)
          CJAC(1,2) = -X(1) + PT49
        END IF
      END IF

*
      RETURN
      END

```

9.2 Program Data

E04UQF Example Program Data

44	2										:Values of M and N
1	1										:Values of NCLIN and NCNLN
1.0	1.0										:End of matrix A
0.49	0.49	0.48	0.47	0.48	0.47	0.46	0.46	0.45	0.43	0.45	
0.43	0.43	0.44	0.43	0.43	0.46	0.45	0.42	0.42	0.43	0.41	
0.41	0.40	0.42	0.40	0.40	0.41	0.40	0.41	0.41	0.40	0.40	
0.40	0.38	0.41	0.40	0.40	0.41	0.38	0.40	0.40	0.39	0.39	:End of Y
0.4	-4.0	1.0	0.0								:End of BL

```

1.0E+25  1.0E+25  1.0E+25  1.0E+25  :End of BU
0.4    0.0                                :End of X
Begin    Example options file for  E04UQF
  Major Iteration Limit   = 15      * (Default = 50)
  Minor Iteration Limit   = 10      * (Default = 50)
End

```

9.3 Program Results

E04UQF Example Program Results

Calls to E04URF

```

Infinite Bound Size = 1.0E+25
Print Level = 1
Verify Level = -1

```

OPTIONS file

```

Begin    Example options file for  E04UQF
  Major Iteration Limit   = 15      * (Default = 50)
  Minor Iteration Limit   = 10      * (Default = 50)
End

```

*** E04UNF

*** Start of NAG Library implementation details ***

```

Implementation title: Generalised Base Version
Precision: FORTRAN double precision
Product Code: FLBAS19D
Mark: 19A

```

*** End of NAG Library implementation details ***

Parameters

Linear constraints.....	1	Variables.....	2
Nonlinear constraints..	1	Subfunctions.....	44
Infinite bound size....	1.00E+25	COLD start.....	
Infinite step size....	1.00E+25	EPS (machine precision)	1.11E-16
Step limit.....	2.00E+00	Hessian.....	NO
Linear feasibility.....	1.05E-08	Crash tolerance.....	1.00E-02
Nonlinear feasibility..	1.05E-08	Optimality tolerance...	3.26E-12
Line search tolerance..	9.00E-01	Function precision....	4.37E-15
Derivative level.....	3	Monitoring file.....	-1
Verify level.....	-1		
Major iterations limit..	15	Major print level.....	1
Minor iterations limit..	10	Minor print level.....	0

J'J initial Hessian....	Reset frequency.....	2
-------------------------	----------------------	---

```
Workspace provided is      IWORK(      100),  WORK(      1000).
To solve problem we need  IWORK(           9),  WORK(           306).
```

Exit from NP problem after 6 major iterations,
8 minor iterations.

Varbl State			Value	Lower Bound	Upper Bound	Lagr Mult	Slack
V	1	FR	0.419953	0.400000	None	.	1.9953E-02
V	2	FR	1.28485	-4.00000	None	.	5.285

L	Con	State	Value	Lower Bound	Upper Bound	Lagr Mult	Slack
L	1	FR	1.70480	1.00000	None	.	0.7048

N Con State			Value	Lower Bound	Upper Bound	Lagr Mult	Slack
N	1	LL	-9.767742E-13	.	None	3.3358E-02	-9.7677E-13

Exit E04UNF - Optimal solution found.

Final objective value = 0.1422983E-01