F02FJF - NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

To find eigenvalues and eigenvectors of a real sparse symmetric or generalized symmetric eigenvalue problem.

2 Specification

SUBROUTINE FO2FJF(N, M, K, NOITS, TOL, DOT, IMAGE, MONIT, NOVECS,

X, NRX, D, WORK, LWORK, RWORK, LRWORK, IWORK,

LIWORK, IFAIL)

INTEGER

N, M, K, NOITS, NOVECS, NRX, LWORK, LRWORK,

IWORK(LIWORK), LIWORK, IFAIL

real

TOL, DOT, X(NRX,K), D(K), WORK(LWORK),

RWORK(LRWORK)

EXTERNAL

DOT, IMAGE, MONIT

3 Description

F02FJF finds the m eigenvalues of largest absolute value and the corresponding eigenvectors for the real eigenvalue problem

$$Cx = \lambda x \tag{1}$$

where C is an n by n matrix such that

$$BC = C^T B \tag{2}$$

for a given positive-definite matrix B. C is said to be B-symmetric. Different specifications of C allow for the solution of a variety of eigenvalue problems. For example, when

$$C = A$$
 and $B = I$ where $A = A^T$

the routine finds the m eigenvalues of largest absolute magnitude for the standard symmetric eigenvalue problem

$$Ax = \lambda x. (3)$$

The routine is intended for the case where A is sparse.

As a second example, when

$$C = B^{-1}A$$

where

$$A = A^T$$

the routine finds the m eigenvalues of largest absolute magnitude for the generalized symmetric eigenvalue problem

$$Ax = \lambda Bx. \tag{4}$$

The routine is intended for the case where A and B are sparse.

The routine does not require C explicitly, but C is specified via a user-supplied routine IMAGE which, given an n element vector z, computes the image w given by

$$w = Cz$$
.

For instance, in the above example, where $C = B^{-1}A$, routine IMAGE will need to solve the positive-definite system of equations Bw = Az for w.

To find the m eigenvalues of smallest absolute magnitude of (3) we can choose $C = A^{-1}$ and hence find the reciprocals of the required eigenvalues, so that IMAGE will need to solve Aw = z for w, and correspondingly for (4) we can choose $C = A^{-1}B$ and solve Aw = Bz for w.

A table of examples of choice of IMAGE is given in Table 1. It should be remembered that the routine also returns the corresponding eigenvectors and that B is positive-definite. Throughout A is assumed to be symmetric and, where necessary, non-singularity is also assumed.

Eigenvalues Required	Problem		
	$Ax = \lambda x \; (B = I)$	$Ax = \lambda Bx$	$ABx = \lambda x$
Largest	Compute $w = Az$	Solve $Bw = Az$	Compute $w = ABz$
Smallest (Find $1/\lambda$)	Solve $Aw = z$	Solve $Aw = Bz$	Solve $Av = z$, $Bw = v$
Furthest from σ (Find $\lambda - \sigma$)	Compute $w = (A - \sigma I)z$	Solve $Bw = (A - \sigma B)z$	Compute $w = (AB - \sigma I)z$
Closest to σ (Find $1/(\lambda - \sigma)$)	Solve $(A - \sigma I)w = z$	Solve $(A - \sigma B)w = Bz$	Solve $(AB - \sigma I)w = z$

The matrix B also need not be supplied explicitly, but is specified via a user-supplied routine DOT which, given n element vectors z and w, computes the generalized dot product w^TBz .

F02FJF is based upon routine SIMITZ (see Nikolai [1]), which is itself a derivative of the Algol procedure ritzit (see Rutishauser [4]), and uses the method of simultaneous (subspace) iteration. (See Parlett [2] for description, analysis and advice on the use of the method.)

The routine performs simultaneous iteration on k > m vectors. Initial estimates to $p \le k$ eigenvectors, corresponding to the p eigenvalues of C of largest absolute value, may be supplied by the user to F02FJF. When possible k should be chosen so that the kth eigenvalue is not too close to the m required eigenvalues, but if k is initially chosen too small then F02FJF may be re-entered, supplying approximations to the k eigenvectors found so far and with k then increased.

At each major iteration F02FJF solves an r by r ($r \le k$) eigenvalue sub-problem in order to obtain an approximation to the eigenvalues for which convergence has not yet occurred. This approximation is refined by Chebyshev acceleration.

4 References

- [1] Nikolai P J (1979) Algorithm 538: Eigenvectors and eigenvalues of real generalized symmetric matrices by simultaneous iteration ACM Trans. Math. Software 5 118–125
- [2] Parlett B N (1980) The Symmetric Eigenvalue Problem Prentice-Hall
- [3] Rutishauser H (1969) Computational aspects of F L Bauer's simultaneous iteration method Numer. Math. 13 4–13
- [4] Rutishauser H (1970) Simultaneous iteration method for symmetric matrices Numer. Math. 16 205–223

5 Parameters

1: N — INTEGER Input

On entry: n, the order of the matrix C.

Constraint: $N \geq 1$.

F02FJF.2 [NP3086/18/pdf]

2: M — INTEGER Input/Output

On entry: m, the number of eigenvalues required.

Constraint: $M \geq 1$.

On exit: m', the number of eigenvalues actually found. It is equal to m if IFAIL = 0 on exit, and is less than m if IFAIL = 2, 3 or 4. See Section 6 and Section 8 for further information.

3: K — INTEGER Input

On entry: the number of simultaneous iteration vectors to be used. Too small a value of K may inhibit convergence, while a larger value of K incurs additional storage and additional work per iteration.

Suggested value: K = M + 4 will often be a reasonable choice in the absence of better information.

Constraint: $M < K \le N$.

4: NOITS — INTEGER

Input/Output

On entry: the maximum number of major iterations (eigenvalue sub-problems) to be performed. If $NOITS \leq 0$, then the value 100 is used in place of NOITS.

On exit: the number of iterations actually performed.

5: TOL-real Input

On entry: a relative tolerance to be used in accepting eigenvalues and eigenvectors. If the eigenvalues are required to about t significant figures, then TOL should be set to about 10^{-t} . d_i is accepted as an eigenvalue as soon as two successive approximations to d_i differ by less than $(|\tilde{d}_i| \times \text{TOL})/10$, where \tilde{d}_i is the latest approximation to d_i . Once an eigenvalue has been accepted, then an eigenvector is accepted as soon as $(d_i f_i)/(d_i - d_k) < \text{TOL}$, where f_i is the normalised residual of the current approximation to the eigenvector (see Section 8 for further information). The values of the f_i and d_i can be printed from routine MONIT. If TOL is supplied outside the range $(\epsilon, 1.0)$, where ϵ is the machine precision, then the value ϵ is used in place of TOL.

6: DOT — real FUNCTION, supplied by the user.

 $External\ Procedure$

DOT must return the value $w^T B z$ for given vectors w and z. For the standard eigenvalue problem, where B = I, DOT must return the dot product $w^T z$.

Its specification is:

1: IFLAG — INTEGER

Input/Output

On entry: IFLAG is always non-negative.

On exit: IFLAG may be used as a flag to indicate a failure in the computation of w^TBz . If IFLAG is negative on exit from DOT, then F02FJF will exit immediately with IFAIL set to IFLAG. Note that in this case DOT must still be assigned a value.

2: N — INTEGER

On entry: the number of elements in the vectors z and w and the order of the matrix B.

3: Z(N) - real array On entry: the vector z for which $w^T Bz$ is required. Input

On entry: the vector z for which w Bz is required

4: $W(N) - real \operatorname{array}$

Input

On entry: the vector w for which w^TBz is required.

5: RWORK(LRWORK) - real array

LRWORK — INTEGER 6:

IWORK(LIWORK) — INTEGER array 7:

8: LIWORK — INTEGER User Workspace Input

User Workspace

Input

DOT is called from F02FJF with the parameters RWORK, LRWORK, IWORK and LIWORK as supplied to F02FJF. The user is free to use the arrays RWORK and IWORK to supply information to DOT and to IMAGE as an alternative to using COMMON.

DOT must be declared as EXTERNAL in the (sub)program from which F02FJF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

IMAGE — SUBROUTINE, supplied by the user.

External Procedure

IMAGE must return the vector w = Cz for a given vector z.

Its specification is:

SUBROUTINE IMAGE(IFLAG, N, Z, W, RWORK, LRWORK, IWORK, LIWORK)

INTEGER IFLAG, N, LRWORK, IWORK(LIWORK), LIWORK

realZ(N), W(N), RWORK(LRWORK)

IFLAG — INTEGER

Input/Output

On entry: IFLAG is always non-negative.

On exit: IFLAG may be used as a flag to indicate a failure in the computation of w. If IFLAG is negative on exit from IMAGE, then F02FJF will exit immediately with IFAIL set to IFLAG.

N — INTEGER 2:

On entry: n, the number of elements in the vectors w and z, and the order of the matrix C.

Z(N) - real array

Input

On entry: the vector z for which Cz is required.

W(N) - real array

Output

On exit: the vector w = Cz.

RWORK(LRWORK) — real array 5:

User Workspace

6: LRWORK — INTEGER

 \bar{Input} User Workspace

7: IWORK(LIWORK) — INTEGER array

LIWORK — INTEGER

Input

IMAGE is called from F02FJF with the parameters RWORK, LRWORK, IWORK and LIWORK as supplied to F02FJF. The user is free to use the arrays RWORK and IWORK to supply information to IMAGE and DOT as an alternative to using COMMON.

IMAGE must be declared as EXTERNAL in the (sub)program from which F02FJF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

MONIT — SUBROUTINE, supplied by the user.

External Procedure

MONIT is used to monitor the progress of F02FJF. MONIT may be the dummy subroutine F02FJZ if no monitoring is actually required. (F02FJZ is included in the NAG Fortran Library and so need not be supplied by the user. The routine name F02FJZ may be implementation dependent: see the Users' Note for your implementation for details.) MONIT is called after the solution of each eigenvalue sub-problem and also just prior to return from F02FJF. The parameters ISTATE and NEXTIT allow selective printing by MONIT.

Its specification is:

SUBROUTINE MONIT(ISTATE, NEXTIT, NEVALS, NEVECS, K, F, D)

INTEGER ISTATE, NEXTIT, NEVALS, NEVECS, K

real F(K), D(K)

1: ISTATE — INTEGER

Input

On entry: ISTATE specifies the state of F02FJF and will have values as follows:

ISTATE = 0

No eigenvalue or eigenvector has just been accepted.

ISTATE = 1

One or more eigenvalues have been accepted since the last call to MONIT.

ISTATE = 2

One or more eigenvectors have been accepted since the last call to MONIT.

ISTATE = 3

One or more eigenvalues and eigenvectors have been accepted since the last call to MONIT.

ISTATE = 4

Return from F02FJF is about to occur.

2: NEXTIT — INTEGER

Input

On entry: the number of the next iteration.

3: NEVALS — INTEGER

Input

On entry: the number of eigenvalues accepted so far.

4: NEVECS — INTEGER

Input

On entry: the number of eigenvectors accepted so far.

5: K — INTEGER

Input

On entry: k, the number of simultaneous iteration vectors.

6: F(K) - real array

Innut

On entry: a vector of error quantities measuring the state of convergence of the simultaneous iteration vectors. See the parameter TOL of F02FJF above and Section 8 for further details. Each element of F is initially set to the value 4.0 and an element remains at 4.0 until the corresponding vector is tested.

7: $D(K) - real \operatorname{array}$

Innu

On entry: D(i) contains the latest approximation to the absolute value of the *i*th eigenvalue of C.

MONIT must be declared as EXTERNAL in the (sub)program from which F02FJF is called. Parameters denoted as *Input* must **not** be changed by this procedure.

9: NOVECS — INTEGER

Input

On entry: the number of approximate vectors that are being supplied in X. If NOVECS is outside the range (0,K), then the value 0 is used in place of NOVECS.

10: X(NRX,K) — real array

Input/Output

On entry: if $0 < \text{NOVECS} \le K$, the first NOVECS columns of X must contain approximations to the eigenvectors corresponding to the NOVECS eigenvalues of largest absolute value of C.

Supplying approximate eigenvectors can be useful when reasonable approximations are known, or when the routine is being restarted with a larger value of K. Otherwise it is not necessary to supply approximate vectors, as simultaneous iteration vectors will be generated randomly by the routine.

On exit: if IFAIL = 0, 2, 3 or 4, the first m' columns contain the eigenvectors corresponding to the eigenvalues returned in the first m' elements of D (see below); and the next k - m' - 1 columns contain approximations to the eigenvectors corresponding to the approximate eigenvalues returned in the next k - m' - 1 elements of D. Here m' is the value returned in M (see above), the number of eigenvalues actually found. The kth column is used as workspace.

11: NRX — INTEGER Input

On entry: the first dimension of the array X as declared in the (sub)program from which F02FJF is called.

Constraint: $NRX \geq N$.

12: D(K) - real array

Output

On exit: if IFAIL = 0, 2, 3 or 4, the first m' elements contain the first m' eigenvalues in decreasing order of magnitude; and the next k-m'-1 elements contain approximations to the next k-m'-1 eigenvalues. Here m' is the value returned in M (see above), the number of eigenvalues actually found. D(k) contains the value e where (-e,e) is the latest interval over which Chebyshev acceleration is performed.

13: WORK(LWORK) — real array

Work space

14: LWORK — INTEGER

Input

On entry: the dimension of the array WORK as declared in the (sub)program from which F02FJF is called.

Constraint: LWORK $\geq 3 \times K + \max(K \times K, 2 \times N)$.

15: RWORK(LRWORK) — real array

User Workspace

RWORK is not used by F02FJF, but is passed directly to routines DOT and IMAGE and may be used to supply information to these routines.

16: LRWORK — INTEGER

Input

On entry: the dimension of the array RWORK as declared in the (sub)program from which F02FJF is called.

Constraint: LRWORK ≥ 1 .

17: IWORK(LIWORK) — INTEGER array

User Workspace

IWORK is not used by F02FJF, but is passed directly to routines DOT and IMAGE and may be used to supply information to these routines.

18: LIWORK — INTEGER

Input

On entry: the dimension of the array IWORK as declared in the (sub)program from which F02FJF is called.

Constraint: LIWORK ≥ 1 .

19: IFAIL — INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error or gives a warning (see Section 6).

For this routine, because the values of output parameters may be useful even if IFAIL $\neq 0$ on exit, users are recommended to set IFAIL to -1 before entry. It is then essential to test the value of IFAIL on exit. To suppress the output of an error message when soft failure occurs, set IFAIL to 1.

F02FJF.6 [NP3086/18/pdf]

6 Error Indicators and Warnings

Errors or warnings specified by the routine:

IFAIL < 0

A negative value of IFAIL indicates an exit from F02FJF because the user has set IFLAG negative in DOT or IMAGE. The value of IFAIL will be the same as the user's setting of IFLAG.

IFAIL = 1

```
On entry, N < 1,

or M < 1,

or M \ge K,

or K > N,

or NRX < N,

or LWORK < 3 \times K + max(K \times K, 2 \times N),

or LRWORK < 1,

or LIWORK < 1.
```

IFAIL = 2

Not all the requested eigenvalues and vectors have been obtained. Approximations to the rth eigenvalue are oscillating rapidly indicating that severe cancellation is occurring in the rth eigenvector and so M is returned as (r-1). A restart with a larger value of K may permit convergence.

IFAIL = 3

Not all the requested eigenvalues and vectors have been obtained. The rate of convergence of the remaining eigenvectors suggests that more than NOITS iterations would be required and so the input value of M has been reduced. A restart with a larger value of K may permit convergence.

IFAIL = 4

Not all the requested eigenvalues and vectors have been obtained. NOITS iterations have been performed. A restart, possibly with a larger value of K, may permit convergence.

IFAIL = 5

This error is very unlikely to occur, but indicates that convergence of the eigenvalue sub-problem has not taken place. Restarting with a different set of approximate vectors may allow convergence. If this error occurs the user should check carefully that F02FJF is being called correctly.

7 Accuracy

Eigenvalues and eigenvectors will normally be computed to the accuracy requested by the parameter TOL, but eigenvectors corresponding to small or to close eigenvalues may not always be computed to the accuracy requested by the parameter TOL. Use of the routine MONIT to monitor acceptance of eigenvalues and eigenvectors is recommended.

8 Further Comments

The time taken by the routine will be principally determined by the time taken to solve the eigenvalue sub-problem and the time taken by the routines DOT and IMAGE. The time taken to solve an eigenvalue sub-problem is approximately proportional to nk^2 . It is important to be aware that several calls to DOT and IMAGE may occur on each major iteration.

As can be seen from Table 1, many applications of F02FJF will require routine IMAGE to solve a system of linear equations. For example, to find the smallest eigenvalues of $Ax = \lambda Bx$, IMAGE needs to solve equations of the form Aw = Bz for w and routines from Chapter F01 and Chapter F04 of the NAG Fortran Library will frequently be useful in this context. In particular, if A is a positive-definite variable

band matrix, F04MCF may be used after A has been factorized by F01MCF. Thus factorization need be performed only once prior to calling F02FJF. An illustration of this type of use is given in the example program.

An approximation \tilde{d}_h , to the *i*th eigenvalue, is accepted as soon as \tilde{d}_h and the previous approximation differ by less than $|\tilde{d}_h| \times \text{TOL}/10$. Eigenvectors are accepted in groups corresponding to clusters of eigenvalues that are equal, or nearly equal, in absolute value and that have already been accepted. If d_r is the last eigenvalue in such a group and we define the residual r_i as

$$r_j = Cx_j - y_r$$

where y_r is the projection of Cx_j , with respect to B, onto the space spanned by x_1, x_2, \ldots, x_r and x_j is the current approximation to the jth eigenvector, then the value f_i returned in MONIT is given by

$$f_i = \max \|r_j\|_B / \|Cx_j\|_B \quad \|x\|_B^2 = x^T B x$$

and each vector in the group is accepted as an eigenvector if

$$(|d_r|f_r)/(|d_r|-e) < \text{TOL}$$

where e is the current approximation to $|\tilde{d}_k|$. The values of the f_i are systematically increased if the convergence criteria appear to be too strict. See Rutishauser [4] for further details.

The algorithm implemented by F02FJF differs slightly from SIMITZ (Nikolai [1]) in that the eigenvalue sub-problem is solved using the singular value decomposition of the upper triangular matrix R of the Gram-Schmidt factorization of Cx_r , rather than forming R^TR .

9 Example

To find the four eigenvalues of smallest absolute value and corresponding eigenvectors for the generalized symmetric eigenvalue problem $Ax = \lambda Bx$, where A and B are the 16 by 16 matrices

F02FJF.8 [NP3086/18/pdf]

$$B = -\frac{1}{2} \begin{pmatrix} -2 & 1 & & & & & & & & & & & & \\ 1 & -2 & 1 & & & & & & & & & & \\ & 1 & -2 & 1 & & & & & & & & \\ & & 1 & -2 & 1 & & & & & & & \\ & & & 1 & -2 & 1 & & & & & & \\ & & & & 1 & -2 & 1 & & & & & \\ & & & & & 1 & -2 & 1 & & & & \\ & & & & & & 1 & -2 & 1 & & & \\ & & & & & & & 1 & -2 & 1 & & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & & & 1 & -2 & 1 & \\ & & & & & & & & & & & & 1 & -2 & 1 \\ & & & & & & & & & & & & & & \\ \end{pmatrix}$$

TOL is taken as 0.0001 and 6 iteration vectors are used. F11JAF is used to factorize the matrix A, prior to calling F02FJF, and F11JCF is used within IMAGE to solve the equations Aw = Bz for w. Details of the factorization of A are passed from F11JAF to F11JCF by means of the COMMON block BLOCK1.

Output from MONIT occurs each time ISTATE is non-zero. Note that the required eigenvalues are the reciprocals of the eigenvalues returned by F02FJF.

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
FO2FJF Example Program Text
Mark 19 Revised. NAG Copyright 1999.
.. Parameters ..
                 NMAX, LA, LRWORK, KMAX, LWORK, LIWORK, NRX
INTEGER
PARAMETER
                  (NMAX=16, LA=10*NMAX, LRWORK=1, KMAX=6,
                 LWORK=5*KMAX+2*NMAX,LIWORK=2*LA+7*NMAX+1,
                 NRX=NMAX)
INTEGER
                 NIN, NOUT
                  (NIN=5, NOUT=6)
PARAMETER
.. Scalars in Common ..
INTEGER
                 NNZ
.. Arrays in Common ..
real
                 A(LA)
INTEGER
                 ICOL(LA), IPIV(NMAX), IROW(LA), ISTR(NMAX+1)
.. Local Scalars ..
real
                 DSCALE, DTOL, TOL
INTEGER
                 I, IFAIL, J, K, L, LFILL, M, N, NNZC, NOITS,
                 NOVECS, NPIVM
                 MIC, PSTRAT
CHARACTER
.. Local Arrays ..
real
                 D(NMAX), RWORK(LRWORK), WORK(LWORK), X(NRX,KMAX)
INTEGER
                 IWORK (LIWORK)
.. External Functions ..
real
EXTERNAL
                 DOT
.. External Subroutines ..
                 FO2FJF, FO2FJZ, F11JAF, IMAGE
EXTERNAL
.. Common blocks ..
COMMON
                 /BLOCK1/A, IROW, ICOL, IPIV, ISTR, NNZ
.. Executable Statements ..
```

```
WRITE (NOUT,*) 'F02FJF Example Program Results'
  Skip heading in data file
  READ (NIN,*)
  READ (NIN,*) N, M, K, TOL
  WRITE (NOUT,*)
   IF (N.LT.5 .OR. N.GT.16) THEN
     WRITE (NOUT,99999) 'N is out of range. N =', N
  ELSE IF (M.LT.1 .OR. M.GE.K .OR. K.GT.KMAX) THEN
     WRITE (NOUT,99999) 'M or K out of range. M =', M, ' K =', K
  ELSE
     Set up the sparse symmetric coefficient matrix A.
     L = 0
     DO 20 I = 1, N
         IF (I.GE.5) THEN
           L = L + 1
            A(L) = -0.25e0
            IROW(L) = I
           ICOL(L) = I - 4
         END IF
         IF (I.GE.2) THEN
           L = L + 1
            A(L) = -0.25e0
            IROW(L) = I
           ICOL(L) = I - 1
         END IF
         L = L + 1
         A(L) = 1.0e0
         IROW(L) = I
         ICOL(L) = I
20
     CONTINUE
     NNZ = L
     Call F11JAF to find an incomplete Cholesky factorisation of A.
     LFILL = 2
     DTOL = 0.0e0
     MIC = 'Modified'
     DSCALE = 0.0e0
     PSTRAT = 'Markowitz'
     IFAIL = 1
     CALL F11JAF(N,NNZ,A,LA,IROW,ICOL,LFILL,DTOL,MIC,DSCALE,PSTRAT,
                  IPIV,ISTR,NNZC,NPIVM,IWORK,LIWORK,IFAIL)
     IF (IFAIL.NE.O) THEN
         WRITE (NOUT, 99999) 'F11JAF fails. IFAIL =', IFAIL
     ELSE
         Call FO2FJF to find eigenvalues and eigenvectors.
         IFAIL = 1
         * To obtain monitoring information from the supplied
         subroutine MONIT, replace the name FO2FJZ by MONIT in
         the next statement, and declare MONIT as external \ast
         NOITS = 1000
         NOVECS = 0
```

F02FJF.10 [NP3086/18/pdf]

```
*
            CALL FO2FJF(N,M,K,NOITS,TOL,DOT,IMAGE,FO2FJZ,NOVECS,X,NRX,D,
                        WORK, LWORK, RWORK, LRWORK, IWORK, LIWORK, IFAIL)
            IF (IFAIL.NE.O) THEN
               WRITE (NOUT,99999) 'Warning - FO2FJF returns IFAIL =',
                 IFAIL
            END IF
            IF (IFAIL.GE.O .AND. IFAIL.NE.1 .AND. IFAIL.LE.4 .AND. M.GE.
               1) THEN
               DO 40 I = 1, M
                  D(I) = 1.0e0/D(I)
   40
               CONTINUE
               WRITE (NOUT,*) 'Final results'
               WRITE (NOUT,*)
               WRITE (NOUT,*) ' Eigenvalues'
               WRITE (NOUT, 99998) (D(I), I=1, M)
               WRITE (NOUT,*)
               WRITE (NOUT,*) ' Eigenvectors'
               WRITE (NOUT, 99998) ((X(I,J), J=1,M), I=1,N)
            END IF
         END IF
     END IF
  60 STOP
99999 FORMAT (1X,A,I5,A,I5)
99998 FORMAT (1X,1P,4e12.3)
     F.ND
     real FUNCTION DOT(IFLAG,N,Z,W,RWORK,LRWORK,IWORK,LIWORK)
     This function implements the dot product - transpose(W)*B*Z.
     DOT assumes that N is at least 3.
      .. Scalar Arguments ..
     INTEGER
                        IFLAG, LIWORK, LRWORK, N
      .. Array Arguments ..
                       RWORK(LRWORK), W(N), Z(N)
     real
     INTEGER
                        IWORK (LIWORK)
     .. Local Scalars ..
     real
     INTEGER
      .. Executable Statements ..
     S = 0.0e0
     S = S + (Z(1)-0.5e0*Z(2))*W(1)
     S = S + (-0.5e0*Z(N-1)+Z(N))*W(N)
     DO 20 I = 2, N - 1
         S = S + (-0.5e0*Z(I-1)+Z(I)-0.5e0*Z(I+1))*W(I)
  20 CONTINUE
     DOT = S
     RETURN
     END
     SUBROUTINE IMAGE(IFLAG, N, Z, W, RWORK, LRWORK, IWORK, LIWORK)
     This routine solves A*W = B*Z for W.
     The routine assumes that {\tt N} is at least 3.
     A, IROW, ICOL, IPIV, ISTR and NNZ must be as returned by routine
     F11JAF.
      .. Parameters ..
                      NMAX, LA, LWORK
      INTEGER
```

```
PARAMETER
                   (NMAX=16, LA=10*NMAX, LWORK=6*NMAX+120)
   .. Scalar Arguments ..
                  IFLAG, LIWORK, LRWORK, N
  INTEGER
   .. Array Arguments ..
  real
                   RWORK(LRWORK), W(N), Z(N)
  INTEGER
                   IWORK(LIWORK)
   .. Scalars in Common ..
  INTEGER
                  NNZ
   .. Arrays in Common ..
  real
         A(LA)
                  ICOL(LA), IPIV(NMAX), IROW(LA), ISTR(NMAX+1)
  INTEGER
   .. Local Scalars ..
           RNORM, TOL
  real
  INTEGER IFAIL, ITN, J, MAXITN CHARACTER*2 METHOD
  .. Local Arrays ..
                  RHS(NMAX), WORK(LWORK)
  .. External Functions ..
            X02AJF
  real
  EXTERNAL
                  XO2AJF
   .. External Subroutines ..
  EXTERNAL
                  F11JCF
  .. Common blocks ..
  COMMON
                   /BLOCK1/A, IROW, ICOL, IPIV, ISTR, NNZ
   .. Executable Statements ..
  Form B*Z in RHS and initialize W to zero.
  RHS(1) = Z(1) - 0.5e0*Z(2)
  W(1) = 0.0e0
  RHS(N) = -0.5e0*Z(N-1) + Z(N)
  W(N) = 0.0e0
  DO 20 J = 2, N - 1
     RHS(J) = -0.5e0*Z(J-1) + Z(J) - 0.5e0*Z(J+1)
     W(J) = 0.0e0
20 CONTINUE
  Call F11JCF to solve the equations A*W = B*Z.
  METHOD = 'CG'
  TOL = XO2AJF()
  MAXITN = 100
  IFAIL = 1
  CALL F11JCF(METHOD, N, NNZ, A, LA, IROW, ICOL, IPIV, ISTR, RHS, TOL, MAXITN,
              W, RNORM, ITN, WORK, LWORK, IFAIL)
  IF (IFAIL.GT.0) IFLAG = -IFAIL
  RETURN
  END
  SUBROUTINE MONIT(ISTATE, NEXTIT, NEVALS, NEVECS, K, F, D)
  Monitoring routine for FO2FJF.
   .. Parameters ..
  INTEGER
                 NOUT
  PARAMETER
                  (NOUT=6)
   .. Scalar Arguments ..
   INTEGER
                   ISTATE, K, NEVALS, NEVECS, NEXTIT
```

F02FJF.12 [NP3086/18/pdf]

```
.. Array Arguments ..
                      D(K), F(K)
      .. Local Scalars ..
     INTEGER
      .. Executable Statements ..
      IF (ISTATE.NE.O) THEN
         WRITE (NOUT,*)
         WRITE (NOUT,99999) ' ISTATE = ', ISTATE, ' NEXTIT = ', NEXTIT
         WRITE (NOUT, 99999) ' NEVALS = ', NEVALS, ' NEVECS = ', NEVECS
         WRITE (NOUT,*) '
                               F
         WRITE (NOUT,99998) (F(I),D(I),I=1,K)
     END IF
     RETURN
99999 FORMAT (1X,A,I4,A,I4)
99998 FORMAT (1X,1P,e11.3,3X,e11.3)
     END
```

9.2 Program Data

```
FO2FJF Example Program Data
16 4 6 0.0001
```

9.3 Program Results

```
FO2FJF Example Program Results
```

Final results

Eigenvalues

```
5.488E-01
           5.900E-01 5.994E-01 6.850E-01
Eigenvectors
1.189E-01 -2.153E-01 1.648E-01 -1.561E-01
-1.378E-01 1.741E-01 1.858E-01 1.931E-01
1.389E-01 1.626E-01 -1.763E-01 -3.005E-01
-1.343E-01 -1.602E-01 -2.227E-01 2.058E-01
2.012E-01 -3.217E-01 3.010E-01 -1.253E-01
-2.235E-01 2.761E-01 2.954E-01 7.440E-02
2.242E-01 2.692E-01 -2.899E-01 -2.312E-01
-2.093E-01 -2.914E-01 -3.320E-01 1.018E-01
2.093E-01 -2.914E-01 3.320E-01 1.018E-01
-2.242E-01 2.692E-01 2.899E-01 -2.312E-01
2.235E-01 2.761E-01 -2.954E-01 7.439E-02
-2.012E-01 -3.217E-01 -3.010E-01 -1.253E-01
1.343E-01 -1.602E-01 2.227E-01 2.058E-01
-1.389E-01 1.626E-01 1.763E-01 -3.005E-01
          1.741E-01 -1.858E-01
1.378E-01
                                 1.931E-01
-1.189E-01 -2.153E-01 -1.648E-01 -1.561E-01
```

[NP3086/18/pdf] F02FJF.13~(last)